

Category6 UTP/STP Lockable Patch Cord

Category 6 UTP/STP patch Cords are manufactured using high quality unshielded/shielded four pair category 6 standard cable, and feature cable strain relief boots with a plug latch protection cap. Additionally its's having key lock protection to avoid the link connectivity & it's highly recommendable for datacenter solution. This patch cord when used with high performance modern category 6 connectivity (solid UTP/STP cable, patch panels and work area outlets), provide superior performance capabilities of high bandwidth (Gigabit 1000Base-T and 1000Base-Tx) applications support.

Features

- Quality 24 AWG standards flexible cable
- High grade 50μ gold plated RJ45 connectors
- Injection molded boot/strain relief boot for improved strain relief
- Soft latch-cover design for easy depression

Technical Specifications

Parameter		Values
Conductor	AWG	24
	Size mm	7/0.195±0.01
	Material	Stranded Bare Copper
Insulation	Material	PE
	Thickness mm	0.155
Jacket	External OD	5.99±0.3
	Material	LSZH

LOCK-PLUG

LOCK-INSERT

PLUG-SOS

LOCK PLUG INSTRUCTION MANUAL

PATENTED

A : How to install Lock-Plug

cut off the latch

1

fix with Lock-Plug

2

completed

3

B : How to secure Lock-Plug into port

put into jack directly

1

done

2

C : How to release Lock-Plug

push the key to bottom

pull out the plug & key together

release the key

D : How to exchange Lock-Plug & Plug-SOS

for regular function

LOCK-INSERT

put into jack directly (release way as the same as Lock Plug)

LOCK-INSERT

E : How to secure Lock-Insert

put into jack directly (release way as the same as Lock Plug)

LOCK-INSERT

⚠ WARNING

proper length

✓

too short / long

✗

skewed

✗

always check for proper fixing of the latch or it can cause jam in the jack !

✓ ✗

always remove the key from Lock Plug to avoid clip part elastic fatigue

✓ ✗

if clip part elastic fatigue, bend the clip outward

trim away any part of boot or Lock Plug to get the best matching

if high density jack does not clip, use thumb to push black area to lock

may not be suitable for some top opened, too high, or special jacks

Ordering Information

Part Code	Description
3C-C6WL-XXYY-ZZ	Cat6 UTP/STP Lockable Patch Cord
3C-C6L-W-KY	Key

W- (U-Unshielded, S-Shielded)

XX-Boot Type (MT-Molded Boot, BT-Boot)

YY- Color(WT-White, YL-Yellow, RD-Red, BL-Blue, GR-Green)

ZZ-Length(1M-1 Meter, 2M-2 Meter, 3M-3 Meter, 5M -5 Meter)

*Customized Length is also available.

Telephone: 080-6888 8018, Email: sales@3c3.in

Com Core Connexions Pvt. Ltd.