

Category 6 RJ45 Angled Keystone Jack

Category 6 RJ45 Angled 45° keystone jacks help to have a better cable management in high-density copper solution. It confirm to ANSI/TIA/EIA-568AB.2.2001 standards. These has to be installed only in 3C3® staggered jack panel.

Features

- Saves space compared to traditional angled panels
- 180° Termination
- Angled jack features easy termination
- Compatible with 3C3® Rapid termination tool solutions
- Easily route cables into vertical cable managers, reducing the need for horizontal or front cable management

Technical Specification

Parameter	Value
Housing Material	Fire Proof ABS UL94V-0
IDC Pin	Bronze and Tinned
Jack Material	8P8C 50micron inches Gold plated
IDC Cap	Fire Proof ABS UL94V-0
IDC Body	Fire Proof ABS UL94V-0
Jack Insertion Cycle	Over 2000 Cycles(min)
IDC Punch Down Cycle	Over 250 Cycles(min)
Operating Temperature	-40°C ~ +70°C

Electrical Specification

- Insulation Resistance: 500M ohms (min)
- Contact Resistance: 20m ohms (Max)
- Current Rating: 1.5 Amps
- DC Resistance: 0.1 ohms (max)
- Withstanding Voltage: 1000 VACRMS @ 60Hz/ 1 min

Ordering Information

Part Code	Description
3C-C6AJ-XX	Category 6 RJ45 Angled Keystone Jack

XX→ (WT-white & BK-Black)

