

## Category 6 UTP Patch Cord

Cat6 UTP/STP Patch cords are manufactured using high quality un-shielded/Shielded 4 Pair Standard cable and features cable strain relief boot with plug latch production cap. These high performance components available in broad range of lengths. They are designed to meet or exceed Cat6 specifications. Conductors are securely mated with shielded/unshielded RJ45 plug Design to deliver superior performance.

### Features

- Quality 24 AWG standards flexible cable
- High grade 50μ gold Plated RJ45 connectors
- Injection molded boot/Strain Relief Boot for improved strain relief
- Soft latch-cover design for easy depression

### Technical Specifications

Parameter	Value	
Conductors	AWG	24
	Size mm	7/0.195±0.01
	Material	Stranded Bare copper
Insulation	Diameter mm	0.94±0.05
	Material	PE
	Thickness mm	0.155
Jacket	External OD	5.99±0.3
	Material	LSZH

### Conformance

- ETL Verified
- RoHS
- UL Certified

### Ordering Information

Part Code	Description
3C-C6W-XXYY-ZZ	Category 6 UTP Patch Cord

W-(U-Unshielded, S-Shielded), XX-Boot Type (MT-Molded Boot,BT-Boot)

YY- Color(WT-White,YL-Yellow,RD-Red,BL-Blue,GR-Green)

ZZ-Length(1M- 1 meter, 2M- 2 meter, 3M- 3 meter, 5M- 5 meter)

\*Customized length is also available

