

## Category 6A F/F Twisted Pair Patch Cords

FTP Patch cords delivers optimal transmission and networking performance with reduced insertion loss and Alien Cross Talk. Stranded bare copper conductors insulated with foam thermoplastics polyolefin. Two insulated conductors twisted together to form a pair shielded with Aluminium Polyester tape. Four such pairs cabled to form the basic unit. Tinned copper braiding overall the 4 pairs. Overall Jacket with LSZH Compound.

### Features

- Quality 26 AWG standards flexible cable
- High grade 50μ gold Plated RJ45 connectors
- Injection molded / Booted for improved strain relief
- Soft latch-cover design for easy depression

### Technical Specifications

Parameter	Values	
Conductors	AWG	26
	Diameter(mm)	7/0.15±0.01 mm
	Material	Stranded Bare copper
Insulation	Diameter mm	1.05±0.05 mm
	Material	PE
	Thickness mm	0.275
Shield	Tinned Copper drain wire	7/0.16mm
	Type(each pair shielded)	Aluminium Polyester Tape
	Type(Overall braiding)	Aluminium Polyester Tape
Jacket	External OD (mm)	6.32 ± 0.3 (mm)
	Material	LSZH

### Ordering Information

Part Code	Description
3C-6AS-GY-XX	Category 6A F/F Twisted Pair Patch Cords

XX- Length in meters



Intertek