


Fiber Optic Adapter - APC

ETISALAT PRODUCT APPROVAL	
EPA No:	780722-4
Approval valid	25 July 2022
Authorized signatory	<i>[Signature]</i>
Designation: D/DST/D&SHS	Date: 26-07-2021



Fiber Optic adapters have high precision alignment sleeves for reliability and improved Stability. For single mode applications a zirconia ceramic sleeve is used to ensure a high precision alignment. The housing is available in green color. A protective cap is provided at each end of the adaptor with green or black color.

Features

- Conformance to ANSI/TIA-568.3-D, IEC 61754-4
- Zirconia ceramic sleeve for high precision alignment
- Low insertion loss and high return loss
- RoHS compliant materials
- SC, LC, ST, FC and Hybrid Adapters are available in both simplex/duplex variants
- Available in metal or plastic housing, Flangeless and Flange options
- Covered under 3C3[®] Performance Warranty

Technical Specifications

Fiber Type	:	Single Mode
Insertion Loss	:	≤0.2dB
Mating Durability (1000 cycles)	:	≤0.2dB
Operating Temperature	:	-40 to +85°C

Ordering Information

Product Code	Description
82CD7	Fiber Optic Adapter C - (0-SCA, 1- LCA) D - (0-SCA, 1- LCA)