

# Fiber Optic Pigtailes - APC

ETISALAT PRODUCT APPROVAL	
EPA No:	780722-2
Approval valid	25 July 2022
Authorized signatory	
Designation	D/DST/D6SHS
Date	26-07-2021



Fiber Optic pigtail are used in permanent connection between patch panel and incoming cables. Pigtailes are pre-constructed with connectors. Connector options include LC, SC, FC, ST, MTRJ, and E2000. These are based on 900micron tight buffered cores and suitable for internal use only.

## Features

- Conformance to ANSI/TIA-568.3-D, ITU-T G.657.A1 (Compatible with G.652.D), IEC 61300-3-4, IEC 61300-3-6, IEC 60874-1, Telcordia GR-326
- All Assemblies Comes with Factory test reports
- Bend insensitive fibers.
- LSZH jacket, meets IEC-60332 (LSZH) flame rating for standard safety compliant.
- Available in APC
- Temperature Rating -40 ~ +85 ° C
- Covered under 3C3® Performance Warranty

## Technical Specifications

Type	:	Single Mode
Insertion Loss	:	≤0.2dB
Return Loss	:	≥60dB (APC)
Repeatability	:	≤0.1dB
Durability	:	≤0.2dB, 1000mattings
Ferrule Material	:	Zirconia Ceramic

## Ordering Information

Product Code	Description
82C91-0015	High Link Fiber Optic Pigtail, OS2 C : Connector 1 (0-SCA, 1- LCA, 6-FCA)