


MPO Patch Cord



MPO Fiber Cabling System is ideally suited for a high density environment that demands space saving and innovative cable management solutions. The MPO connector is a high performance connector with multiple engineered product enhancements to improve optical and mechanical performance

Features

- Conformance to Telcordia GR-1435 Core, ANSI/TIA-568.3-D, ANSI/TIA 604-5, IEC 61754-7
- High precision guide pins for exact alignment
- Plug and Play
- High Density interconnect
- Removable housing for quick change of pin clamps and easy ferrule cleaning/re-polishing
- Single-Mode and Multi-Mode color coded housings
- Alignment achieved with high precision guide pins
- Push/Pull mating for quick assembly
- Covered under 3C3® Performance Warranty

Technical Specifications

Type	Wavelength	I.L Type	I.L Max	R.L Min
MPO /PC (MM)	850n/1300nm	0.25dB	0.35dB	≥30dB
MPO/PC (SM)	1310/1550nm	0.25dB	0.35dB	≥50dB
MPO/APC (SM)	1310/1550nm	0.25dB	0.35dB	≥60dB

MPO Patch Cord

Note:

- Fiber type available in SM (G.652D, G.657A1, G.657A2) & in MM (OM2, OM3, OM4)
- Polarity available in Straight (Type-A). Cross (Type B) or Pair Flip (Type C)
- Optional Polarity and Gender changeable connectors are available.

Ordering Information

Product Code

67CDE-XXXX

Description

MPO to MPO Patch Cord

C : (0-OS2, 1-OM3, 2-OM4)

D : (0- Universal Polarity, 1- F to F, 3- M to F, 5-M to M)

E : (0- Universal Polarity, 1- 12F Type A, 2- 12F Type B,

3- 12F Type C, 4- 8F Type A, 5- 8F Type B, 6-8F Type C)

XXXX – Length in Decimeter (0010-1M ~9990-999M)