

Fiber Optic Multi Mode Pigtail



Fiber Optic pigtail is used in permanent connection between patch panel and incoming cables. Pigtails are pre-constructed with connectors. Connector options include LC, SC, FC, ST, MTRJ, and E2000. These are based on 900micron tight buffered cores and suitable for internal use only.

Features

- Complies to ANSI/TIA-568.3-D, IEC 61300-3-4, IEC 61300-3-6, IEC 60874-1 & ISO/ IEC 11801
- LSZH jacket, meets IEC-60332-1 (LSZH) flame rating for standard safety compliant.
- All Assemblies comes with Factory test reports
- Bend insensitive fibers
- Available in OM2, OM3 & OM4
- Available in PC, UPC
- Covered under 3C3® Performance Warranty

Technical Specifications

Type	:	Multi Mode
Insertion Loss	:	≤0.3dB
Return Loss	:	≥35dB (UPC)
Repeatability	:	≤0.1dB
Durability	:	≤0.2dB, 1000mattings
Ferrule Material	:	Zirconia Ceramic
Operating Temperature	:	-40°C ~ +85°C

Regulatory Compliances/Certifications

- RoHS Certified

Ordering Information

Product Code
7BC01-0015

Description

High Link Fiber Optic Single Mode Pigtail, 1.5M
B = (1-LC, 3-SC, 5-ST, 6-FC)
C = Type (2- OM2, 3-OM3, 4-OM4)