

DIN Rail Fiber Patch Panel



DIN Rail mount fiber patch panel is designed either to support direct termination or fusion splicing of the fibers. The materials used for the patch panel is of high quality anodized aluminum with natural finishes which makes it light weight and compact in size. The compact size of the DIN Rail mount patch panel helps to save space especially when it is mounted within enclosures or cabinet with other DIN Rail mount equipment. The patch panel can be loaded with a variety of adaptors like ST, SC, FC and LC. It can support up to 12 cores when fully loaded with adaptors based on the connector.

Features

- Space-Saving installation
- DIN-Rail mountable
- Up to 12 ports
- Covered under 3C3® Performance Warranty

Specifications

- Material - Anodized Aluminum
- Dimensions: 140 x 41 x 110 mm
- Operating Temperature: -10°C to +70°C

Ordering Information

| Part Code | Description |
|------------|--|
| 61907-0000 | DIN Rail Patch Panel, Unloaded |
| 61CD7-00XX | DIN Rail Patch Panel, Loaded with Duplex Adapters, Pigtailed C = (0 – OS2, 2 – OM2, 3 – OM3, 4 – OM4) D = Coupler Type (2= LC 4= SC) XX = Number of Cores (06- 6 Cores, 12- 12 Cores) |