

Fiber Panel Adapter Plate



The adaptor plates are preloaded with coupler and can snap in for installation and can be removed easily for future changes. Blank future expansion adapter plate reserves fiber adaptor panel space for future use

Features

- Flexible configuration, fast Installation
- Unloaded adapter plate for future expansion or Blank plate options
- Pull buckle fixed for easy access
- Suitable for LC Duplex, SC Duplex
- High Precision of Mechanical Dimensions
- Available for 4 Cutout, 2 Cutout & DIN Rail
- Available for OS2, OM2, OM3 & OM4
- Covered under 3C3[®] Performance Warranty

Technical Specifications

Insertion Loss (Typical)	:	Single Mode <0.3dB Multi Mode <0.5dB
Durability	:	≤0.1dB, 1000 times
Maximum Capacity	:	6 LC Duplex, 3 SC Duplex
Operating Temperature	:	-25°C ~ +70°C

Fiber Panel Adapter Plate

Ordering Information

Product Code

63CD4-X
63CD6-X
63CD3-X
63CD5-X
63CD9-X

Description

Adapter Plate Loaded for 4cutout Fiber Panel,
Adapter plate Unloaded for 4cutout Fiber Panel
Adapter Plate Loaded for 2cutout Fiber Panel,
Adapter plate Unloaded for 2cutout Fiber Panel
Adapter plate Loaded for DIN Rail Panel
C : Type (0- OS2, 2-OM2, 3-OM3, 4-OM4)
D : Adapter (2-LC Duplex, 4-SC Duplex)
X : Adapter Count (3- 3 Adapter, 6- 6 Adapter)
63904-0 Blank Adapter plate for 4cutout Fiber Panel
63903-0 Blank Adapter plate for 2cutout Fiber Panel