

Fiber Optic Patch Panel Wall Mountable 6F/12F/24F



Wall Mount Fiber Optic Patch Panel with lockable system are recommended for secured high density terminations allowing economical interconnection of fibers for indoor or wall space limitations. Loaded panel comes with adaptor plates, splice management and Pigtaills.

Features

- Conformance to ANSI/TIA-568.3-D, Telcordia GR-326-CORE, Telcordia GR-1221-CORE, ISO/IEC 11801, IEC 61754 & IEC 61300 series
- Space Saving with its compact & small design of enclosure
- Front door design is easy for operation & Fibers expansion
- Can Manage both splices and terminations
- Can include adapter panels for maximum 24 fiber cores of LC/SC/ST/FC terminations
- Snap-in locker design, easy to change adapter plates for flexible configuration & easy installation
- 8 Nos of \varnothing 20mm cable entries at top and bottom
- Lockable for added security
- Dimension (H x W x D): (300 X 230 X 100) mm
- Color: Light Grey
- Covered under 3C3[®] Performance Warranty

Technical Specifications

Panel Material	:	SPCC (Cold rolled steel sheet)
Form Factor	:	19" 1U Rack Mount
Dimension	:	483 x 250 x 44.45 mm
Color	:	Black
Pigtail Types	:	Single Mode Multi Mode
Insertion Loss	:	≤0.2dB ≤0.3dB
Return Loss	:	≥50dB (UPC) ≥35dB
Repeatability	:	≤0.1dB
Durability	:	≤0.2dB, 1000mattings
Ferrule Material	:	Zirconia Ceramic
Operating Temperature	:	-25°C ~ +70°C

Ordering Information

Product Code	Description
61905-0000	Fiber Panel Wall Mount, Single door, Unloaded
61CD5-0XXX	Fiber Panel Wall Mount, Single door, Loaded with Adapter Plate, Pigtails and Splice Tray. C : Type (0- OS2, 1-OM2, 2-OM2, 3-OM3, 4-OM4) D : Adapter (2-LC Duplex, 4- SC Duplex) XXX- Core (006- 6core, 012-12core, 024-24core)