

## 2 Post Open Frame Network Rack



3C3<sup>®</sup> 2 post Open racks are designed for high density datacenters and Networking center applications. The racks vertical frames are made up of aluminum profiles with the power coated and bolted.

### Features

- Conforms to the DIN 41494 and ISO 9001-2015 Standards
- 6061-T6 aluminum extrusion construction gives the light weight and high strength
- U positions are graduated with ascending numbers (1U=44.45mm)
- Horizontal Panel Mounting Holes are with M6 threads in both flanges
- M6 tapped holes are conductive as per the DIN 41494 standard
- Powder Coated provides uniform appearance and protection against aluminum Corrosion
- Weight capacity of 1200Kgs Static load
- Grounding provision is made

### Technical Specifications

|                    |   |                                   |
|--------------------|---|-----------------------------------|
| Construction       | : | CKD (Knock down)                  |
| Basic Frame        | : | Aluminum Sections                 |
| Equipment Mounting | : | DIN 41494 Standard M6 Taped holes |
| Standard Finish    | : | Powder coated                     |
| Standard Color     | : | RAL 9005 Black                    |
| Static Load        | : | 1200kg                            |

### Accessories to be ordered separately

Cable Manager  
Hardware mounting Kit  
Earthing Kit  
PDU

## 2 Post Open Frame Network Rack

### Ordering Information

| <b>Product Code</b> | <b>Description</b>   |
|---------------------|--|
| 43200-XXXX          | 2 post Open Network Rack<br>XXXX= Height in U<br>0036 = 36U<br>0042 = 42U<br>0045 = 45U<br>0047 = 47U  |
| 439DE-XXXX          | Vertical Cable Manager for Open Rack<br>D = 3 Vertical Cable Manager Front & Back<br>4 Vertical Cable Manager Front only<br>E = Dimension - Width * Depth in inches<br>If D = 3<br>0 = 4"x8" (4" Front, 4" Back)<br>1 = 6"x12" (6" Front, 6" Back)<br>If D = 4<br>2 = 4" x4 "<br>3 = 6"x6"<br>XXXX = Height in U<br>0036 = 36U<br>0042 = 42U<br>0045 = 45U<br>0047 = 47U |
| 43911-0020          | Hardware Mounting Kit, M6 Screws 20Nos/pack  |
| 43921               | Earthing Kit (19" Horizontal)  |
| 433DE-2XXX          | PDU, Horizontal,2U<br>D = Input plug type<br>0 = 5Amp Indian Standard Plug<br>1 = 15Amp Indian standard Plug<br>E = Output<br>0 = 6 ways 5Amp Indian Standard Socket<br>1 = 6 ways 15Amp Indian Standard Socket<br>2 = 6 ways 5/15Amp Indian Standard Socket<br>XXX= Power cord length in decimeter (010 – 1m)   |